

GLASSWASHERS

ECOLINE series - Electronic

UG505 range - Basket 500x500 mm

NEW PRODUCT



Supplied with
2 flat-bottomed polypropylene basket, PB50G01

TECHNICAL FEATURES

- Single skinned construction in AISI 304 stainless steel
- Double skinned insulated door
- Moulded tank with rounded corners
- Moulded basket guides
- Combined wash and rinse arm with quick release system
- Boiler with drain pipe for complete draining
- Thermostop for guaranteed rinse water temperature
- 'Stand-by' function of the heating elements during idle periods
- Self cleaning cycle available as standard
- Break tank as standard
- Self-diagnosis system with error messages
- Peristaltic detergent and rinse aid pumps with electrical adjustment as standard

WASHING FEATURES

- Wash system: Wash pump with 'Soft Start' system
- Rinse system: Atmospheric boiler and rinse pump (HTR system)
- Drain system: Automatic drain pump with partial water exchange in the wash tank
- Filter system: Integral plastic tank filter with double stage filtration in the sump and additional micro filter for pump protection
- 3 wash programs: P1 90", P2 150", P3 240"
- FRESH WATER function for complete wash tank water replacement after each wash cycle
- EXTRA-RINSE function for a prolonged rinse

	UG505DUK	UG505DSUK
Basket dimension	500x500mm	500x500mm
Control panel	Electronic	Electronic
Baskets / hour	40 / 24 / 15	40 / 24 / 15
Usable wash height	365 mm	365 mm
Water consumption per cycle	3.2 lt	3.2 lt
Softener with automatic regeneration	-	Included
Tank: capacity / heating element	13 lt / 2.0 kW	13 lt / 2.0 kW
Boiler: capacity / heating element	6 lt / 5 kW	6 lt / 5 kW
Power supply / Power installed	230V 1N 50Hz / 5.7kW switchable to 400V 3N 50Hz / 5.7kW, 230V 1N 50Hz / 4.0kW, 230V 1N 50Hz / 2.7kW	230V 1N 50Hz / 5.7kW switchable to 400V 3N 50Hz / 5.7kW, 230V 1N 50Hz / 4.0kW, 230V 1N 50Hz / 2.7kW
Dimensions (WxDxH)	580x600x820 mm	580x600x820 mm

Find the complete range of professional dishwashers 

 **smeg**
FOODSERVICE